

MODEL EGCS-A2/B2 ACCELEROMETER


SPECIFICATIONS

- ◆ Critically Damped
- ◆ DC Response
- ◆ Temperature Compensated
- ◆ High Sensitivity, Amplified

The Model EGCS-A2 & -B2 accelerometers are critically damped with built-in over-range stops that are set to protect the unit against 10,000g shocks. The accelerometers incorporate signal conditioning with optional $\pm 5Vdc$ or $\pm 2.5Vdc$ amplified full-scale output and are offered in ranges from $\pm 5g$ to $\pm 5000g$. The accelerometers are ideal for low frequency measurements and feature temperature compensation from $+20$ to $+80$ °C.



dimensions




FEATURES


- ◆ $\pm 5g$ to $\pm 5000g$ Dynamic Range
- ◆ Heavy Duty, Rugged
- ◆ Static and Dynamic Measurement
- ◆ DC to 4000Hz Frequency Response
- ◆ $\pm 1\%$ Non-Linearity
- ◆ -40 °C to $+120$ °C Temperature Range
- ◆ 10,000g Over-range Protection

APPLICATIONS

- ◆ Road Vehicle Testing
- ◆ Machine Control
- ◆ Downhole
- ◆ Engine Testing
- ◆ General Purpose



It is recommended that "0V COMMON" of the power supply be grounded if consistent with proper operation of the instrumentation system.



Common mode output voltage of $+5V$ nom. referred to -Input

PERFORMANCE SPECIFICATIONS

All values are typical at +24°C, 100Hz and 15Vdc excitation unless otherwise stated. Measurement Specialties reserves the right to update and change these specifications without notice. Standard product parameters are described in PSC-1004 for Plug & Play DC Accelerometers.

Parameters

DYNAMIC

	±5	±10	±25	±50	±100	±250	±500	±1000	±2500	±5000	Notes
Range (g)											
Sensitivity, A2 Spec (mV/g)	1000	500	200	100	50	20	10	5	2	1	
Sensitivity, B2 Spec (mV/g)	500	250	100	50	25	10	5	2.5	1	0.5	
Frequency Response min. (Hz)	0-80	0-120	0-240	0-350	0-500	0-750	0-1000	0-1500	0-2000	0-2400	±1/2dB
Frequency Response nom. (Hz)	0-150	0-200	0-400	0-600	0-900	0-1300	0-1750	0-2500	0-3500	0-4000	±1/2dB
Natural Frequency (Hz)	300	400	800	1200	1800	2600	3500	5000	7000	8000	
Non-Linearity (%FSO)	±1	±1	±1	±1	±1	±1	±1	±1	±1	±1	
Transverse Sensitivity (%)	<3	<3	<3	<3	<3	<3	<3	<3	<3	<3	
Damping Ratio	0.7	0.7	0.7	0.7	0.7	0.7	0.7	0.7	0.7	0.7	Nominal
Shock Limit (g)	500	1000	2000	5000	10000	10000	10000	10000	10000	10000	

ELECTRICAL

Zero Acceleration Output (mV)	±250										Differential
Excitation Voltage (Vdc)	A2: ±15Vdc, B2: 24-32Vdc (28Vdc nominal)										
Excitation Current (mA)	15mA maximum										
Full Scale Output Voltage (Vdc)	A2: ±5Vdc, B2: ±2.5Vdc										
Output Impedance (Ω)	A2: 1_ nominal, B2: 1000_ nominal										
Insulation Resistance (MΩ)	>100										
Ground Isolation	Isolated from Mounting Surface										

ENVIRONMENTAL

Thermal Zero Shift	±50mV / 50°C (±50mV / 100°F)
Thermal Sensitivity Shift	±2.5% / 50°C (±2.5% / 100°F)
Operating Temperature Compensated	-40 to +120°C (-40 to +250°F) +20 to +80°C (+70 to +170°F), contact factory for other temperature compensation options
Storage Temperature	-40 to +120°C (-40 to +250°F)
Humidity	Epoxy Sealed

PHYSICAL

Case Material	Anodized Aluminum
Cable	PFA Insulated Leads, Braided Shield, Silicone Jacket
Weight	<15 grams
Mounting	Screw Mount
AWG	#28

Wiring color code: +Excitation = Red; -Excitation = Black; +Output = Green; -Output = White

Calibration supplied: CS-FREQ-0100 NIST Traceable Amplitude Calibration from 20Hz to ±1/2dB Frequency Response Limit

The information in this sheet has been carefully reviewed and is believed to be accurate; however, no responsibility is assumed for inaccuracies. Furthermore, this information does not convey to the purchaser of such devices any license under the patent rights to the manufacturer. Measurement Specialties, Inc. reserves the right to make changes without further notice to any product herein. Measurement Specialties, Inc. makes no warranty, representation or guarantee regarding the suitability of its product for any particular purpose, nor does Measurement Specialties, Inc. assume any liability arising out of the application or use of any product or circuit and specifically disclaims any and all liability, including without limitation consequential or incidental damages. Typical parameters can and do vary in different applications. All operating parameters must be validated for each customer application by customer's technical experts. Measurement Specialties, Inc. does not convey any license under its patent rights nor the rights of others.

MODEL EGCS-A2/B2 ACCELEROMETER

ORDERING INFO

EGCS – A2 – 100 – /Z1/L2M/C
to +170°F)

| | | Options, otherwise leave blank
| | Range (100 is 100g)
| Specification (A2 or B2)
contact factory

Compensated Temp Ranges:

Standard = +20 to +80°C +(70

Excitation Voltage:

Z* = Non standard, contact factory
Standard = A2: ±15Vdc, B2: 28Vdc
V* = Non standard,

Special Cable Length:

L00F = Replace "00" with length in feet
L00M = Replace "00" with length in meter
C = Microtech type male or equivalent

Connector Wired to Cable:

Example: EGCS-A2-100-/L2M

Model EGCS, A2 Specifications, 100g Range, 2 Meter Cable Length

The information given herein, including drawings, illustrations and schematics which are intended for illustration purposes only, is believed to be reliable. However, TE Connectivity makes no warranties as to its accuracy or completeness and disclaims any liability in connection with its use. TE Connectivity's obligations shall only be as set forth in TE Connectivity's Standard Terms and Conditions of Sale for this product and in no case will TE Connectivity be liable for any incidental, indirect or consequential damages arising out of the sale, resale, use or misuse of the product. Users of TE Connectivity products should make their own evaluation to determine the suitability of each such product for the specific application.