

MODEL 4020 & 4030 ACCELEROMETER



SPECIFICATIONS

- ◆ DC Response, Silicon MEMS
- ◆ Dual & Triaxial Output Options
- ◆ Low Cost, Great Value
- ◆ $\pm 2g$ & $\pm 6g$ Measurement Range
- ◆ Rugged Construction

The Model 4020 & 4030 are low noise, signal conditioned DC accelerometers packaged in a durable molded housing. The accelerometers are offered in $\pm 2g$ & $\pm 6g$ ranges with a nominal 0-200Hz bandwidth. The model 4020 is a dual axis configuration (X&Y axes) while model 4030 is a triaxial configuration. The capacitive silicon MEMS sensing element offers high resolution and long term stability for critical measurement applications.

FEATURES

- ◆ 5-30Vdc Excitation Voltage
- ◆ Environmentally Sealed
- ◆ Low Pass Filtered Output
- ◆ Capacitive Silicon MEMS Element
- ◆ Integral #24 AWG Cable
- ◆ Self-Test Enabled

APPLICATIONS

- ◆ Low Frequency Vibration Monitoring
- ◆ Tilt & Inclination Measurement
- ◆ Motion Measurements
- ◆ Structural Monitoring
- ◆ Laboratory Testing

PERFORMANCE SPECIFICATIONS

All values are typical at +24°C, 80Hz and 10Vdc excitation unless otherwise stated. TE Connectivity reserves the right to update and change these specifications without notice.

Parameters

DYNAMIC

			Notes
Range (g)	±2	±6	
Sensitivity (mV/g)	1000	333	±10%
Frequency Response (Hz)	0-200	0-200	±5%
Non-Linearity (%FSO)	±1	±1	
Transverse Sensitivity (%)	<3	<3	
Shock Limit (g)	2000	2000	
Residual Noise (µV RMS)	600	240	Passband
Residual Noise (µg/√Hz RMS)	42	51	
Self Test Output Change (mV)	X = +210 ±90 Y = -210 ±90 Z = -340 ±190	X = +70 ±30 Y = -70 ±30 Z = -110 ±65	Ground ST Lead

ELECTRICAL

Zero Acceleration Output (V)	2.5 ±0.1
Excitation Voltage (Vdc)	5 to 30
Excitation Current (mA)	4
Full Scale Output Voltage (Vdc)	±2
Ground Isolation	Isolated from Mounting Surface

ENVIRONMENTAL

Thermal Zero Shift (%FSO)	±4	-40° to +85°C
Thermal Sensitivity Shift (%)	±5	-40° to +85°C
Operating Temperature (°C)	-40 to 85	
Humidity	Epoxy Sealed, IP65	


PHYSICAL

Housing Material	Nylon 6-6, 30% GF Molded Housing
Weight (grams)	50 (cable not included)
Mounting	2x ¼ or M6 Screws
Mounting Torque	18 lb-in (2.0 N-m)


Optional accessories: 121 3-Channel Precision Low Noise DC Amplifier

MODEL 4020 & 4030 ACCELEROMETER

DIMENSIONS



SCHEMATIC



ORDERING INFORMATION

4020 (biaxial) or 4030 (triaxial)	G G G	Z Z Z
Series Type		
Range		
002=2g		
006=6g		
Cable length		
120=120 inches		
240=240 inches		
360=360 inches		
197=197 inches, 5 meters		
394=394 inches, 10 meters		

Example; 4030-002-120
Model 4030 (triaxial), 2g range, 120inch (10ft) cable length

Example; 4020-002-120
Model 4020 (biaxial), 2g range, 120inch (10ft) cable length

The information given herein, including drawings, illustrations and schematics which are intended for illustration purposes only, is believed to be reliable. However, TE Connectivity makes no warranties as to its accuracy or completeness and disclaims any liability in connection with its use. TE Connectivity's obligations shall only be as set forth in TE Connectivity's Standard Terms and Conditions of Sale for this product and in no case will TE Connectivity be liable for any incidental, indirect or consequential damages arising out of the sale, resale, use or misuse of the product. Users of TE Connectivity products should make their own evaluation to determine the suitability of each such product for the specific application.